

## TECHNICAL DATA SHEET

# LM-17PRO / LM-19PRO

Professional TFT LCD Flat Screen Monitors



LM-17 PRO



LM-19 PRO

### KEY FEATURES

- "A" Grade TFT LCD Panel
- Double Coated Glass Front
- Looping Function (2 BNC Inputs and 2 BNC Outputs)
- VGA, S-Video and HDMi Inputs
- 4H Comb Filter (For Better Image Quality)
- 3D Noise Reduction
- De-Interlace
- Fast Response Time (5ms)
- Audio Input
- Internal Speakers
- Active Matrix Technology
- VESA Compatible
- On-Screen Display Menu
- Desk Stand (Detachable)
- Includes DC 12V PSU

### ORDERING INFORMATION

- LM-17PRO 17" TFT LCD Professional TFT LCD Monitor  
LM-19PRO 19" TFT LCD Professional TFT LCD Monitor

## TECHNICAL DATA SHEET

### TECHNICAL SPECIFICATION

Model Number	LM-17PRO	LM-19PRO
Resolution	1280 x 1024 (SXGA)	
Brightness	300cd/m2	
Contrast Ratio	800:1	
Aspect Ratio	4:3	
Viewing Angle	U/D: 80°/80° L/R: 80°/80°	U/D: 80°/80° L/R:85°/85°
Response Time	5ms	
Pixel Pitch	0.264(H) x 0.264(V) mm	0.294(H) x 0.294(V) mm
Display Colors	16.2 Million Colours	
Display Mode	Video 1 / Video 2 / PC / HDMI	
Input Interface	Input Signal: Analogue 0.7V Peak to Peak Sync: Separate SYNC (TTL Positive or Negative)	
Composite Input Composite Output	BNC x 2, VGA x 1, RCA x 2, PC Audio x 1, HDMI x 1 BNC x 2	
Auto Adjustment	Yes	
De-Interlace	Yes	
Wall Mount	Yes	
Accessories	Power Cord, Adaptor, VGA Cable	
O.S.D. Control	Picture Mode, Contrast, Brightness, Colour, Tint, Sharpness, Colour Temp, DNR	
TFT LCD Panel	"A" Grade Panel, Double Coated Glass Front	
Speakers	Yes, 2 x 2.5W	
Safety	UL/CUL, FCC-DOC, CE, ROHS	
Power Consumption	35W Max. in "ON" Mode Under 3W in Power Saving Mode (100 Vac) Under 5W in Power Saving Mode (240 Vac)	
Power Supply	DC 12V	
Dimensions (W x H x D)	420 x 420 x 220 mm	430 x 415 x 220 mm
Weight	5.5 Kg	6 Kg

Features and specifications are subject to change for further improvement without any notice