

VISTA VFS-L RANGE OF LITE FLAT SCREEN MONITORS



SAVE ON SPACE, NOT ON STYLE

The VFS-L range of high quality, flat screen monitors come with improved technology to give better contrast and screen refresh rates in 15, 17 and 19" screen sizes. Aimed at mid-end installations where the look of the monitor is as important as the space-saving advantages, they will quickly and easily integrate into any CCTV system.

The intuitive menu system makes them very simple to set-up and comes in English, French, German and Spanish. Front panel key locks stop unwanted adjustment of monitor settings while the combination of a Vesa mount and stand allows the monitors to be mounted anywhere.

A fast response time of down to 5mS reduces blur on movement and the 1000:1 contrast further facilitates sharp images. The range also comes with dual looping BNC connectors, S-Video, and PC and audio connections. The internal clock can be used to give exact usage for any service queries.

To learn more about this product range please visit us at vista-cctv.com



Key Features:

1000:1 contrast

Provides crisp and clear images

Fast response time

Down to 5mS, reducing blur on movement

Composite video and PC input

Allows unit to be used with desktop PC and CCTV systems

Good viewing angles

Up to 170° in horizontal and 160° in vertical

Competitively priced

Excellent performance against cost ratio

Front panel keylock

Protects monitor settings from tampering

Running clock

Gives exact usage time of monitor

THE PROFESSIONAL CHOICE

MODELS IN THIS RANGE

VFS-L15B	15" black case
VFS-L15W	15" white case
VFS-L17B	17" black case
VFS-L17W	17" white case
VFS-L19B	19" black case
VFS-L19W	19" white case

TECHNICAL SPECIFICATION

GENERAL

Inputs 2x composite video looping, 1x S-Video, 1x PC, 1x audio

PANEL

Pixel format	1280(H) x 1024(V), for 17" and 19" 1024(H) x 768 (V) for 15"
Pixel pitch	15" version 0.297nm by 0.297nm 17" version 0.264nm by 0.264nm 19" version 0.294nm by 0.294nm
Colour depth	5" 16.2M colours 17" 16.7M colours 19" 16.7M colours
Contrast	15" 500:1 17" 700:1 19" 1000:1
Response time	15" 8mS 17" 6mS 19" 5mS
Viewing angles	15" 70/70/65/65 17" 80/80/80/80 19" 85/85/80/80
Brightness	15" 250 cd/m ² 17" 300 cd/m ² 19" 300 cd/m ²

COMPOSITE VIDEO

Video mode	PAL/NTSC (auto selection)
Video input	1Vp-p @ 75 ohms
Connectors	2x BNC looping auto terminating 75 ohms

S-VIDEO

Video mode	PAL/NTSC (auto selection)
Video input	0.7Vp-p (luminance), 0.3Vp-p (chrominance)
Connector	4 pin mini din looping auto terminating 57 ohms

PC

Connector	DVI-I
Input resolution	15" VGA, SVGA, XGA 17" VGA, SVGA, XGA, SXGA 19" VGA, SVGA, XGA, SXGA

AUDIO

Speaker	2 off 1 watt
Phone jack	2 off 1.0Vp-p/1 kHz

ELECTRICAL

Power requirement	DC 12V ±5%
Power consumption	15" 24W 17" 34W 19" 39W
Power connectors	mains: IEC320-C13 low voltage: 2.1/5.5mm barrel

PHYSICAL

Case material	Plastic
Dimensions	15" 340x351x190mm (WxHxD) 17" 370x360x190mm (WxHxD) 19" 420x410x190mm (WxHxD)
Weight (net/packing)	15" 2.6kg/4.4kg 17" 3.6kg/5.5kg 19" 3.8kg/5.7kg

CONTROL

User controls	Channel/down/up/menu/power key
OSD languages	English, French, German and Spanish

ASSOCIATED PRODUCTS

Accessories	Power cord, DVI-D-sub cable, stereo audio cable
--------------------	---



No liability will be accepted by Vista for any errors or omissions in this information.

DS-VFSLMonitors-version2